



# LED BULBS

Whichever barn light you choose, our exquisite selection of light bulbs will elevate your design to the next level! Discover our collection of standard LED bulbs alongside unique decorative choices, allowing you to further customize your fixture and express your individual style.

## TALA

- Tinted or Matte Porcelain Finishes
- Suitable to Replace 12W-45W Incandescent
- 2200-2700K Color Temperatures
- Dimmable From 0-100%
- Mouth Blown Glass Construction
- 360° omni-directional beam angle
- Max Temp -5°C to 40°C
- Lifetime 30,000hrs

## GREEN CREATIVE

- Clear, Amber, Opaque or Smoky Finishes
- Suitable to Replace 25W-40W Incandescent
- 2000-4000K Color Temperatures
- Dimmable From 0-100%
- Full Glass Construction
- 330° Omni-directional Beam Angle
- Suitable for use in Wet Locations
- Max Temp -25°C to 45°C
- Lifetime 25,000hrs

28-LURA



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Tinted	T12	4 1/4	1 1/2	0.06	LED	E26	2200	Warm White	21	3	210	70	0.9	110-120	95	Yes

37092



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	ST19	5 3/8	2 1/2	0.09	LED	E26	2100	Warm White	40	4.5	250	56	≥0.7	120	82	Yes

37093



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	ST19	5 3/8	2 1/2	0.09	LED	E26	2000	Warm White	40	4.5	250	56	≥0.7	120	82	Yes

37094



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	ST19	5 3/8	2 1/2	0.09	LED	E26	4000	Cool White	40	4.5	150	33	≥0.7	120	82	Yes

28GLOB



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	A19	4 1/4	2 3/8	0.07	LED	E26	2500	Warm White	48	6	600	100	0.9	110-120	95	Yes

36752



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	A19	4 3/16	2 3/8	0.07	LED	E26	2700	White	75	10	1150	115	≥0.9	120	92	Yes

36084



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Amber	A19	4 3/16	2 3/8	0.07	LED	E26	2700	White	60	7.5	600	80	≥0.7	120	82	Yes

36085



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Silver Bowl	A19	4 3/16	2 3/8	0.07	LED	E26	2700	White	60	7.5	700	93	≥0.7	120	82	Yes

36083



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Frosted	A19	4 3/16	2 3/8	0.07	LED	E26	2700	White	60	9	810	89	≥0.7	120	92	Yes

36070



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	G25	4 5/16	3 1/8	0.09	LED	E26	2700	White	40	3.8	350	92	≥0.	120	92	Yes

36071



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Amber	G25	4 5/16	3 1/8	0.09	LED	E26	2000	Warm White	40	4	250	63	≥0.7	120	82	Yes

36072



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Silver Bowl	G25	4 5/16	3 1/8	0.09	LED	E26	2700	White	40	4.5	400	89	≥0.7	120	82	Yes

28-PORC-II



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Matte Porcelain	G25	4 3/4	3 1/8	0.09	LED	E26	2700	White	45	6	540	90	0.9	110-120	95	Yes

28-ELVA



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Tinted	G30	5 1/2	3 3/4	0.15	LED	E26	2200	Warm White	37	6	420	70	0.9	110-120	95	Yes

37092



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	G40	6 7/8	4 15/16	0.19	LED	E26	2100	Warm White	40	4.5	250	56	≥0.7	120	82	Yes

36073



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	G40	6 7/8	4 15/16	0.19	LED	E26	2700	White	60	5.5	500	90	≥0.7	120	92	Yes

37103



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear & Amber	G40	6 7/8	4 15/16	0.19	LED	E26	2000	Warm White	40	4.5	250	56	≥0.7	120	82	Yes

37105



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear		6 13/16	4 1/16	0.29	LED	E26	2000	Warm White	40	6.5	500	77	≥0.7	120	92	Yes

37104



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	C35	8 1/16	4 5/16	0.38	LED	E26	2000	Warm White	40	6.5	500	77	≥0.7	120	92	Yes

37106



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Amber	T10	7 3/16	1 1/4	0.11	LED	E26	2000	Warm White	40	6.5	450	69	≥0.7	120	82	Yes

28-PORC-II



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Matte Porcelain	G40	6 7/8	4 7/8	0.19	LED	E26	2700	White	45	6	540	90	0.9	110-120	95	Yes

28-NOMA



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Matte Porcelain	BR45	4 1/4	5 1/2	0.37	LED	E26	2700	White	45	6	540	90	0.9	110-120	95	Yes

28-OBLO



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Matte Porcelain	T40	6 1/2	4 1/4	0.37	LED	E26	2700	White	45	6	540	90	0.9	110-120	95	Yes

28-ENNO



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Matte Porcelain	T42	4 1/4	5 1/4	0.34	LED	E26	2700	White	45	6	540	90	0.9	110-120	95	Yes

29-OVAL



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Matte Porcelain	R51	6 3/4	6 3/8	0.36	LED	E26	2700	White	45	6	540	90	0.9	110-120	95	Yes

28-VORN-I



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Tinted	G40	6 7/8	4 7/8	0.35	LED	E26	2200	Warm White	12	2	100	50	0.9	110-120	95	Yes

37102



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Smoky Ombre	E53	10 5/16	6 11/16	0.54	LED	E26	1800	Yellow	25	4.5	110	24	≥0.7	120	82	Yes

28-VORN-II



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Tinted	A52	10 3/4	6 1/2	0.55	LED	E26	2200	Warm White	16	3	150	50	0.9	110-120	95	Yes



37099



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	G63	11 1/16	7 7/8	0.66	LED	E26	2100	Warm White	40	4.5	300	67	≥0.7	120	82	Yes

37100



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Amber	G63	11 1/16	7 7/8	0.66	LED	E26	2000	Warm White	40	4.5	300	67	≥0.7	120	82	Yes

37101



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Smoky	G63	11 1/16	7 7/8	0.66	LED	E26	4000	Cool White	40	4.5	150	33	≥0.7	120	82	Yes

37096



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	A50	11 5/16	6 5/16	0.53	LED	E26	2100	Warm White	40	4.5	300	67	≥0.7	120	82	Yes

37097



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Amber	A50	11 5/16	6 5/16	0.53	LED	E26	2000	Warm White	40	4.5	300	67	≥0.7	120	82	Yes

37098



OFF

ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Smoky	A50	11 5/16	6 5/16	0.53	LED	E26	4000	Cool White	40	4.5	150	33	≥0.7	120	82	Yes

37065



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	B11	3 9/16	1 3/8	0.04	LED	E26	2700	White	60	5.5	500	91	≥0.7	120	92	Yes

37063



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	B11	3 13/16	1 3/8	0.03	LED	E12	2700	White	60	5.5	500	91	≥0.7	120	92	Yes

37056



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Clear	B11	3 13/16	1 3/8	0.03	LED	E12	2700	White	25	2	200	100	≥0.7	120	92	Yes

37059



OFF ON

Finish	Shape	Length (IN)	Width (IN)	Weight (LB)	Light Source	Base	CCT (K)	Color Description	Equiv. (W)	Wattage (W)	Lumens (LM)	Efficacy (LM/W)	Power Factor	Input Voltage	CRI	Dim
Frosted	B11	3 13/16	1 3/8	0.03	LED	E12	2700	White	40	3.3	300	91	≥0.7	120	92	Yes